

WASH EFFECTS

ADJ LED RC4
(Sold Separately)

UC-IR
(Sold Separately)
1321000074

AIRSTREAM IR
1226100319



WiFLY CHAMELEON

1226100320



Compatible with:
ADJ LED RC2
(Sold Separately)

UC-IR
(Sold Separately)
1321000074

AIRSTREAM IR
1226100319

CHAMELEON QBAR PRO

1226100325


Specification

- 3 x 15W RGBA+UV (5-in-1) LEDs
- Rechargeable Lithium battery powered with built-in wireless DMX
- 63 Static Colors
- 6 Operating Modes: RGBA+UV Dimmer Mode, Built-In Program Mode (22 Programs) Auto
- Run Mode, Static Color Mode, Sound Active Mode, & DMX Control
- LED pulse & strobe effect / Electronic Dimming: 0 - 100%
- Tilt: 270-degree / 5-40 degree beam angle
- DMX512 Protocol 3-pin XLR In/Out
- IEC in/out to Daisy Chain Power (Connect up to 14 fixtures max.)
- Power Consumption: 45W
- Rechargeable Lithium battery life: 4.5 Hour Battery Life (Full On in Normal Mode)
- 6 Hour Battery Life (Energy Saving Mode with Full Charge)
- Battery Charge Time: 3 Hours (With LOAD switch Off)
- Multi-voltage Operation: 100-240V, 50Hz/60Hz
- Dimensions (LxWxH): 230x220x168mm / 9" x 8.75" x 6.5"
- Weight: 9 kg. / 4.15 lbs.

Photometric

	0.5m	1m	2m	3m	4m	5m	Beam Angle
S*	0.105	0.21	0.42	0.63	1.05	1.05	
R	2010	663	177.9	72	45.5	28.7	(5.0°)
G	1960	657	173.4	68.6	41.3	22.9	
B	2810	890	194.3	89.7	50.1	29.2	
A	944	339	74.3	32.6	16.3	8.4	
UV	820	303	68.7	24.7	13.3	8.4	
RGBA+UV	9500	1900	427	192	109.7	67.2	

	0.5m	1m	2m	3m	4m	5m	Beam Angle
40°	0.36	0.7	1.4	2.1	2.8	3.5	
R	1197	318	80.6	59.3	22.1	13.1	(15.0°)
G	1174	224	55.6	25.7	14.1	8.9	
B	1190	297	80.8	39.7	22.6	14.1	
A	439	153.6	33.6	14.8	8.6	5.8	
UV	291	72.9	20.5	8.6	4.7	2.9	
RGBA+UV	3360	791	221	89.7	51.2	33.7	



Specification

- Built-in WiFLY Extended Range wireless DMX (up to 2,500 ft/762m)
- Adjustable head to manual change beam direction
- Individual Pixel Control
- 2 x 8 Character LCD Display
- 19 Built-In Programs
- 63 Color Macros
- LED pulse & strobe effect
- Electronic Dimming: 0 - 100%
- Compatible with all ADJ WiFLY fixtures and controllers plus the ADJ LED RC2, UC IR wireless remotes (both remotes sold separately), and Airstream IR
- 7 DMX channel modes 4/5/7/9/10/12/14
- 6 Operating Modes: RGBA Dimmer Mode, Built-In Program Mode (19 Programs), Auto Run Mode, Static Color Mode, Sound Active Mode, & DMX Control
- 15 degree beam angle
- DMX-512 Protocol 3-pin XLR In/Out
- IEC in/out to Daisy Chain Power (Connect up to 6 fixtures max.)
- Power Consumption: 100W
- Multi-voltage Operation: 100-240V, 50Hz/60Hz
- 3 x 30W RGBA (4-in-1) LEDs
- Dimensions (LxWxH): 270 x 100 x 260mm / 10.5" x 4" x 10.25"
- Weight: 8 lbs. / 3.7 kg.

Photometric

	R	D15	580	89.5	40.1	17.5	11.7
G	D15	299	57.1	24.8	13.2	8.7	
B	D15	394	105.4	47.1	18.1	11.6	(5.0°)
W	D15	470	114.2	55.7	29.4	19.2	
A	D15	120.8	28.2	11.8	6.8	4.1	
UV	D15	82.6	21.9	10.4	5.3	3	
RGBA+UV	D15	1163	196	97.3	53.6	33.4	

