



1237000082



1237000130

SWEEPER BEAM QUAD LED

XS 600



Specification

- Light Source: 8 x 8W High Output RGBW (Red, Green, Blue, White) LEDs
- Quick sweeping Beam effect with 270° tilt stepper motors and individual LED cell control
- Extremely sharp 3.5° beam angle;
- DMX Channel Modes : 1, 6, 35, 39
- LED pulse & strobe effect
- 270 degree tilt from smooth Stepper Motors
- 4-Button DMX LED Display
- 3 Operational modes: DMX controller, Master/Slave & Sound Active
- 3 PIN DMX In/Out
- IEC AC In/Out (Power daisy chain 8 units @110V, 14 units @220V)
- Power Consumption: .43 Amps @ 110V; .21 Amps @ 220V
- Dimensions (LxWxH): 38.5" x 3.0" x 5.25" / 973 x 73 x 132mm
- Weight: 13 lbs/ 6.3 kg

Specification

- Unique dual Axis Moving Head with 360° continuous rotation, in both directions
- 3 Operational Modes: DMX control, Show Mode, & Sound Active
- 2 DMX Channel modes: 25 Channels & 31 Channels
- 6 x 10W 4-in-1 RGBW LEDs
- Pixel control of each LED
- Beam Angle: 10 Degree / 360° continuous rotation, in both directions
- Power consumption: 60W
- 3-pin XLR DMX connectors
- I.E.C. In & Out to Daisy chain Power (Connect up to 8 Fixtures)
- Multi-voltage Operation: AC 100-240V 50/60Hz: I.E.C. In
- Dimensions (LxWxH): 7" x 7.75" x 12.5" / 180.2 x 195.6 x 317.7mm
- Weight: 7 lbs. / 3 kgs.

Compatible with UC3 Series
UC3 Universal Controller



UC-IR
(Sold Separately)
1321000074



AIRSTREAM IR
1226100319

Photometric

R	11300	5782	2581	1455	848	(LUX)
G	17100	5272	2093	1120	672	
B	29900	7653	2713	1379	774	
W	15500	5331	2229	1242	740	

