

Application

Beam style	well-defined, flat field profile projection
Suitable for	medium - large scale theatres, arenas, medium to long-throw applications
Specification level	professional range
Beam angle	8° - 22°
Typical throw distance	10 - 45m

Electrical specifications

Supply Volts	230V AC single phase to ballast unit
Max. Lamp Watts	1500W
Lamp base	PGJX50 FastFit
Ballast	external unit, electronic flicker-free ballast with separate pulse ignitor and on/off switch
Fuse	20A, on ballast
Auto-disconnect	no
Cable/connection	2m, multicore cable to ballast; 2m 3x2.5mm ² bare ended cable to power
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Paint/Finish	epoxy powder paint, black
Lamp House Construction	extruded aluminium and sheet steel
Reflector	87,5mm diameter glass
Optical system	double condenser with variable zoom
Mounting & suspension	steel stirrup with 12mm centre hole and DIN mounting. Spigot for ø29mm tube supplied
Control of pan and tilt	two large rubber handles
Weight/Packed weight	19,8kg / 29 kg - ballast: 8,5kg /10,5 kg – kit: 70 kg
Packed volume	0.204m ³ ballast: 0.049m ³
Filter cut size	185 x 185mm
Accessory runners	3 slots
Colour frame	metal, 185 x 185mm, supplied
Lamp access	removable side panel on the lamp-house
Lens access	sliding panels beneath lamp tube

Operational specifications

Focus adjustment	slide zoom controls (dia./softness) at side
Lamp alignment	not requested
Beam shaping	20-leaf iris included; shutters: accessories
Dimming	optical dimmer iris included
Positional adjustment	lever tilt clamp

Lamp types

1500W 6000K	Philips 1500 MSR Gold FastFit PGJX50 750 hrs
-------------	--

LDR recommends Philips lamps

Accessories

Spare metal colour frame	■20100106
5-colour colour changer	■20105106
Spare iris diaphragm	20100707
Gobo holder, A/B size	20100807
Black tripod	20102401
Chrome plated tripod	20102402
Spare spigot ø29mm	20102200
Kit 1-hand control iris/dowser	20107070
Stirrup-kit for suspension	20102900
Flight case with braking wheels	20107180 for f.spot/ballast/col.chang./tripod

Photometric data

Narrow focus		MSR 1500Gold Fast Fit									
Beam dia.	2.5	2.7	2.9	3.1	3.3	3.6	3.8	4.0	4.2	m	
lux	4048	3449	2974	2591	2277	2017	1799	1615	1457		
Distance	24	26	28	30	32	34	36	38	40	m	

Wide focus

Beam dia.	3.2	3.7	4.2	4.7	5.3	5.8	6.3	6.8	7.4	m	
lux	4153	3051	2336	1846	1495	1236	1038	885	763		
Distance	12	14	16	18	20	22	24	26	28	m	

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS


Canto® 1500msr FF

1500W

230V 50/60Hz

discharge followspot

part number : 10867180 Followspot /K10867180 kit



New concept, efficient, lightweight and extremely powerful 1500W discharge followspot for more power at middle-long distance. The MSR filling of the lamp guarantees pure, white light, whereas the short arc provides high beam intensity for professional entertainment lighting.

Canto® 1500 msr FF features the patented FastFit rear load lamp base system, which enables easy lamp replacement in difficult stage conditions.

Canto® 1500 msr FF features an electronic, flicker-free external ballast unit and is delivered complete with two large side control handles, colour frame, 20-leaf iris, mechanical dimmer, spigot and 2m mains cable.

Also available in the kit version, including fitted colour changer, tripod and lamp in flight case



Distribuito da:
AMLUX s.r.l.
46042 Castel Goffredo (MN)
info@amlux.it -
www.amlux.it