### Product datasheet

# Article no.: 341131

Pendant lamp, Kiara, white, 220-240V AC/50-60Hz, 1x max. 40,00 W



### **Technical Data**

General Characteristics	
Material	gypsum
Colour	white
Optics	paintable
included in delivery	



#### **Electrical Characteristics**

Power	1x max. 40,00 W
Input voltage	220-240V AC/50-60Hz
Input current	
Base (standard designation)	E27
Number of bases	1
Power supply unit	
Electronically reversible	dimmable via optional bulb
Connection possibility	clamp
Protection class I, II, III	1



### Product datasheet

# Article no.: 341131

Pendant lamp, Kiara, white, 220-240V AC/50-60Hz, 1x max. 40,00 W



#### **Light Direction**

Rotating and tilting range	fixed
Angle of inclination	0°
Radiation direction	2 Side
Reflector / lense	symmetrisch

#### **Dimensions & Weight**

Length	
Width	
Height	240 mm
Diameter	145 mm
Suspensions from ceiling	3,00 m
Product Weight	1805 g

#### **Base dimensions**

Length	
Width	
Height	30 mm
Diameter	120 mm





### Product datasheet

# Article no.: 341131

Pendant lamp, Kiara, white, 220-240V AC/50-60Hz, 1x max. 40,00 W



### Absolute maximum ratings

Working temperature	-5°C - +40°C
Storage temperature	
IP - Code	IP 20

EEI	The luminaire is suitable for lamps of energy efficiency classes A++ to E.
IP 20	Protection against penetration of foreign objects > 50 mm. No protection against penetration of water.
$\odot$	Gypsum is a natural product and is subject to natural variations in the quality. Dirt and bumps can be removed with the included sandpaper.
	Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.

page 3 of 3