


VERSIONI SPECIALI
SPECIAL VERSION


6000/5

Elettrovalvola diritta con attacchi femmina - maschio
Ingresso: filetto 1/8" femmina gas cilindrico
Uscita: filetto 1/8" maschio gas conico
Straight solenoid valve, female-to-male connections
Inlet: 1/8" female cylindrical gas thread
Outlet: 1/8" male tapered gas thread




6000/6

Elettrovalvola a 90° femmina - femmina 1/8" con parzializzazione della portata 0% - 100%
Ingresso e uscita: filetto 1/8" femmina gas cilindrico
Parzializzazione: con spillo di regolazione con doppio O-ring in FPM e anello di guida Anti-frizione in PTFE, blocco totale dell'uscita, manopola Ø24 mm compresa
90° Solenoid valve with female-to-female connections, 1/8" tap for flow rate control 0% to 100%
Inlet and outlet: 1/8" female cylindrical gas thread
Flow rate control: by means of adjusting needle and double FPM O-ring and sliding ring, PTFE anti-friction device, outlet total lock, Ø24 mm knob included



5388

Elettrovalvola attacco maschio con portagomma a resca uscita in asse e attacco per pressostato
Ingresso: filetto 1/8" maschio gas conico
Attacco pressostato: filetto 1/8" femmina gas cilindrico
Uscita: portagomma a resca Ø7mm
Solenoid valve with male connection and rubber-hose, aligned outlet and pressure sensor connection
Inlet: 1/8" male tapered gas thread
Pressure sensor connection: 1/8" female cylindrical gas thread
Outlet: rubber-hose Ø7mm



5859

Elettrovalvola con cannotto in acciaio smontabile, flangia laterale ingresso/uscita, ispezionabile
Ingresso e uscita: foro Ø3mm con O-ring OR2025
Solenoid valve with removable steel sleeve, inlet/outlet side plate, suitable to be cleaned inside
Inlet and outlet: Ø3mm hole with OR2025 O-ring

