

HAL 12000W 240V

Halogen (> $130\ V$) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

Product family features

- Operation at mains voltage: 230 V | 240 V

- Color temperature: 3,200 K (for professional film and TV work)

- Color temperature: 3,400 K (for maximum luminous efficacy)

Product datasheet

Technical data

General Product Information

| Global order reference | HAL 12000W 240V | |
|------------------------|-----------------|--|
| ANSI code | Other | |

Electrical Data

| Nominal wattage | 12000 W |
|-----------------|---------|
| Nominal voltage | 240 V |

Photometric Data

| Nominal luminous flux | 420000 lm |
|----------------------------------|-----------|
| Color temperature | 3400 K |
| Correlated color temperature CCT | 3319 K |
| Chromaticity coordinate x | 0.416 |
| Chromaticity coordinate y | 0.396 |
| Color rendering index Ra | 100 |

Physical Attributes & Dimensions

| Lamp base | G38 |
|----------------|----------|
| Diameter | 80.0 mm |
| Length | 400.0 mm |
| Product weight | 630.00 g |

Operating Conditions

| Burning position | s45 |
|------------------|-----|
| Dimmable | Yes |

Lifetime Data

| Nominal lifetime | 130 hr |
|------------------|--------|

Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | |
|---|---------------|--|
| Primary article identifier | 4062172409339 | |
| Date of declaration | 01-10-2024 | |
| Declaration no. in SCIP database | In work | |

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4062172409339 | HAL 12000W 240V | Folding carton box 1 | 140 mm x 140 mm x 448 mm | 8.78 dm ³ | 811.00 g |
| 4062172409346 | HAL 12000W 240V | Shipping carton box 6 | 558 mm x 416 mm x 592 mm | 137.42 dm³ | 6227.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.