

MSR Gold™ SA Double Ended

MSR Gold™ 1510 SA/DE 1CT/4

To optimize the total lifetime of the double ended MSR Gold™ SA Double Ended lamps, the caps are plated with gold. This provides superior heat protection and thereby minimizes premature failure of the lamp and lamp holder, as well as ensuring extended consistent performance. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures, which further extends service life and consistency of high-quality light output.

Product data

• General Information

Cap-Base SFC10-4 [SFC10-4]
Operating Position UNIVERSAL [Any or Universal (U)]
Main Application Entertainment
Life To 50% Failures (Nom)

System Description SA/DE

• Light Technical

Color Code - [Not Specified] Luminous Flux 140000 lm (Nom) Chromaticity Coor-326 dinate X (Nom) Chromaticity Coor-336 dinate Y (Nom) Correlated Color 6000 K Temperature (Nom) 93 lm/W Luminous Efficacy (rated) (Nom) Color Rendering Index (Nom)

Operating and Electrical

Power (Rated) 1510 W (Nom)
Lamp Current (Nom) 13.5 A Ignition Supply 198 V Voltage (Min)

Controls and Dimming

Dimmable Yes

• Mechanical and Housing

Cap-Base Information SFC10-4

• Luminaire Design Requirements

Bulb Temperature 950 °C (Max)
Pinch Temperature 500 °C (Max)

• Product Data

Full product code 871829122113500 MSR Gold™ 1510 SA/DE 1CT/4 Order product name EAN/UPC - Product 8718291221135 928176605115 Order code Numerator - Quantity Per Pack Numerator - Packs per outer box Material Nr. (12NC) 928176605115 Net Weight (Piece) 0.034 kg




MSR Gold™ SA Double Ended

Warnings and Safety

 A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing





MSR GOLD 1510 SA/DE

Product	D	0	Α	C (max)
MSR Gold™ 1510 SA/DE 1CT/4	23.2 mm	7.0 mm	114.8 mm	136 mm



Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.