

## HALOPAR 16 35 W 240 V 35° GU10

OSRAM HALOPAR 16 GU10/GZ10 | Halogen lamps with parabolic reflector PAR16, with GU10/GZ10 base



## Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications

#### **Product benefits**

- Brilliant accent light
- With whole glass reflector for brilliant lighting effects
- · Approved for use in open luminaires (to IEC 60598-1)
- · No transformer required
- UV filter
- · Innovative bulb pinch technology for the burner
- Complies with IEC 60432-2 thanks to integrated fuse function
- Contains no mercury, can be thrown away with normal household waste

#### **Product features**

· Average life: 2,000 h

• 100 % dimmable

• Color rendering index R<sub>a</sub>: 100

• Base: GU10, GZ10



### Technical data


### Electrical data

Nominal wattage	35 W	
Nominal voltage	240 V	
Rated wattage	35 W	
Power factor $\lambda$	1.00	
Energy consumption	35 kWh/1000h	

# Light technical data

Nominal useful luminous flux 90°	200 lm	
Luminous intensity	570 cd	
Beam angle	35 °	
Color temperature	2700 K	
Light color as per EN 12464-1	Warm White	
Color rendering index Ra	100	
Starting time	0.0 s	
Warm-up time (60 %)	0.00 s	
Lumen main.fact.at end of nom.life time	0.75	
Rated useful luminous flux 90°	200 lm	

# Dimensions & weight



## Product line drawing

Diameter	51.0 mm
Length	55.0 mm
Overall length	53.0 mm
Outer bulb	PAR51

Maximum diameter	51.0 mm

#### Colors & materials


Lamp mercury content	0.0 mg	
Mercury-free	Yes	

#### Lifespan

Nominal lamp life time	2000 h	
Rated lamp life time	2000 h	
Number of switching cycles	50000 <sup>1)</sup>	

 $<sup>^{1)}</sup>$  At 1 min on / 3 min off

#### Additional product data



#### Spectral power distribution

Base (standard designation)	GU10	
Footnote used only for product	Not suitable for outdoor use or damp conditions	

## **Capabilities**

Burning position	Any	
Dimmable	Yes	

#### Certificates & standards

Energy efficiency class	D
-------------------------	---

## **Country specific categorizations**

ILCOS	HAGS/UB-35-240-GU10-51/35	
Order reference	64820 FL	

# Country specific information

Product code	METEL-Code	SEG number	STK-Number	UK Org
4050300727226	-	8327514	-	-

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321595324	HALOPAR 16 35 W 240 V 35° GU10	Shipping carton box 20	- x - x -		
4050300727240	HALOPAR 16 35 W 240 V 35° GU10	Shipping carton box 20	111 mm x 130 mm x 257 mm	3.71 dm <sup>3</sup>	1036.80 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

For light distribution curves see

www.osram.com

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.