

MSR

MSR 400 1CT/4

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes — in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data

• General Information

Cap-Base GX9.5 [GX9.5]
Operating Position UNIVERSAL [Any or Universal (U)]
Main Application Studio/Disco
Life To 50% Failures (Nom)

Cold Strike

- [Not Specified]

System Description

Light Technical Color Code

Luminous Flux (Min) 28500 lm 32000 lm Luminous Flux (Nom) Chromaticity Coor-325 dinate X (Nom) Chromaticity Coor-320 dinate Y (Nom) Correlated Color 5900 K Temperature (Nom) Luminous Efficacy 80 lm/W (rated) (Nom)

Index (Nom)

Operating and Electrical

Color Rendering

Power (Rated) 400 W

(Nom)

Lamp Current (Nom) 6.9 A

Ignition Supply 207 V Voltage (Min)

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Cap-Base Information

• Luminaire Design Requirements

Bulb Temperature 700 °C (Max)
Pinch Temperature 350 °C (Max)

• Product Data

Full product code
Order product name
EAN/UPC - Product
Order code
Numerator - Quantity Per Pack
Numerator - Packs
per outer box
Material Nr. (12NC)
928077905115

Material Nr. (12NC) 92807790511 Net Weight (Piece) 44.000 g




Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and

remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




GX9.5


MSR 400

 Product
 D
 O
 L
 L
 L
 C
 F
 F
 F

 MSR 400 1CT/4
 23 mm
 6.0 mm
 61 mm
 63 mm
 62 mm
 112 mm
 36 mm
 35 mm
 34 mm



Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.