# MSD Platinum (Touring/ Stage)

# MSD Platinum 5 R 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires - for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

## Product data

#### General Information

Cap-Base Operating Position Main Application Life To 50% Failures (Nom) System Description

UNIVERSAL [ Any or Universal (U)] Stage/Touring 3000 h

Reflector-E20.6

#### • Light Technical

Color Code 2 7100 lm Luminous Flux (Min) Luminous Flux 7950 lm (Nom) Chromaticity Coor-300 dinate X (Nom) Chromaticity Coor-300 dinate Y (Nom) 8000 K Correlated Color Temperature (Nom) Color Rendering Index (Nom)

#### • Operating and Electrical

Power (Rated) 189 W (Nom)

### Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and

- Controls and Dimming Dimmable Yes
- Mechanical and Housing Cap-Base Information
- Luminaire Design Requirements Pinch Temperature 350 °C
- Product Data

(Max)

Full product code Order product name EAN/UPC - Product Order code Numerator - Quan-1 tity Per Pack Numerator - Packs 8 per outer box Material Nr. (12NC) Net Weight (Piece)

872790093070200 MSD Platinum 5 R 1CT/8 8727900930702 928190805314

928190805314 0.120 kg


remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.






# MSD Platinum (Touring/Stage)

## Dimensional drawing



MSD Platinum 5 R					
	Product	D	Т	0	С
	MSD Platinum 5 R 1CT/8	51.4 mm	6.8 mm	1.0 mm	57.1 mm

# Photometric data





 $\ensuremath{\mathbb{C}}$  2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting